



h

TINTORETTO LABEL H+O

description

Uncoated felt-marked paper certify FSC[®], made with E.C.F. pulp. Wet-strength treatment suitable for labelling applications. Available in Gesso and Crema colours. Wet and dry high opacity values (H + O) also for labels.

range

size grain substance
72x101 LG 95

technical features
ref. standard/instrument
unit of measure

substance	VSA	opacity	cobb 60	W.B.R.	Dry tensile strength	
ISO 536	ISO 534	ISO 2471	ISO 535	ISO 3781	ISO 1924	
g/m ²	cm ³ /g	%	g/m ²	%	long±10%	cross±10%
95 ± 3%	1,4	90 ± 2	25 ± 4	≥ 9	6,5	4

Brightness (col. Gesso) - ISO 2470 (R457) - 100% ± 2
Relative Humidity 50% ± 5 ref. TAPPI 502-98

treatment



ecological features



The mark of responsible forestry

ELEMENTAL
CHLORINE
FREE
GUARANTEED



notes


The product is completely biodegradable.
Special runs available upon request.

The Company reserves the right to modify the technological features of the product in relation to market requirements.

Tintoretto Label is an uncoated, felt-marked paper which has been specially developed for the labels sector. For labelling, always observe the correct indications as regards grain direction. It must be parallel to the base of the bottle (see drawings).


applications

Form of the label




wrap-around label

Rolling after wetting the back of the label.



correct grain direction



wrong grain direction

Can be used without problems with the main printing systems: letterpress, offset, blind embossing, hot foil stamping, thermography, screen printing and bronzing. The macro-porous surface requires the use of oxidative drying inks.

printing suggestions

The varnish coated with an offset machine is almost fully absorbed and therefore does not improve gloss or protection. Good results with major processing operations such as: cutting, die-cutting and glueing.

converting suggestions